

MORE FROM WOOD.



Quality Management ISO 9001

Coding: TL ThermalEN
ID1858
Revision: 13
Approved: 22/06/2021

Technical leaflet

Thermal resistance of EGGER Laminate Flooring, Comfort Flooring

Applicability for heated floors and cooled floors

Version	Thermal Resistance DIN EN 12667 R in (m ² K)/W*	Applicability for heated floors (requirement) R < 0.15 (m ² K)/W	Applicability for cooled floors (recommendation) R < 0.10 (m ² K)/W
EGGER Laminate Flooring Aqua+			
8 mm Laminate Flooring Aqua+	0.06	yes**	yes**

Version	Thermal Resistance DIN EN 12667 R in (m ² K)/W*	Applicability for heated floors (requirement) R < 0.15 (m ² K)/W	Applicability for cooled floors (recommendation) R < 0.10 (m ² K)/W
EGGER Laminate Flooring			
6 mm Laminate Flooring	0.05	yes**	yes**
7 mm Laminate Flooring	0.06	yes**	yes**
8 mm Laminate Flooring	0.07	yes**	yes**
10 mm Laminate Flooring	0.08	yes**	yes**
12 mm Laminate Flooring	0.10	yes**	yes**



Responsible: Technical Customer Service